

MarineSeal Series 250UHD WRAPID Outer Cover

An integral component of the UCC MarineSeal Series 250UHD WRAPID System, providing long term corrosion protection for steel substrates in marine environments.

Description	<p>UCC MarineSeal Series 250UHD WRAPID Outer Cover is an integral component of the UCC MarineSeal Series 250UHD System.</p> <p>It is manufactured from XR5 high-performance geo-membrane. It is designed to retain its original physical properties for its full service life.</p> <p>UCC MarineSeal Series 250UHD WRAPID Outer Cover is factory lined with 3000 microns thickness petrolatum coating material.</p>
Uses	UCC MarineSeal Series 250UHD WRAPID Outer Cover provides the armouring outer cover for the MarineSeal Series 250UHD WRAPID Jetty Pile Protection System.
Features	<ul style="list-style-type: none"> - High mechanical strength - High impact strength - Retains physical properties for full service life - Unaffected by saltwater immersion - High hoop tension jacket mitigates against Sulphate Reducing Bacteria - Incredibly fast application sequence, clean pile and install jacket - Factory lined with 3000 microns thickness petrolatum coating material
Application	<ul style="list-style-type: none"> - Prepare surface to St 2 std. - Install MarineSeal Series 250UHD WRAPID Outer Cover.

Properties	Test Method	Value
Total Weight	ISO 2286-2	1100 g / sq.mt 32.4 oz / sq.yd
Yarn (W/F)	ISO 2060	1000 / 1000 Denier 1100 / 1100 Dtex
Threads (W/F)	ISO 1049-2	30 / 30 per inch 12 / 12 per cm
Tensile Strength (W/F)	DIN 53354	440 / 390 kg / 5cm 4312 / 3822 N / 5cm 492 / 436 lbs / in.
Tear Resistance (W/F)	DIN 53363	52 / 48 kg 509.6 / 470 N 115 / 106 lbs

Product Packaging

UCC MarineSeal Series 250UHD WRAPID Outer Cover is a custom fabricated jacket which is sized specifically to suit the project at hand. The maximum Outer Cover length for a single jacket is 6.0m, where access is a concern, stack jackets can be supplied to accommodate access restrictions.