

JointSeal Fabric Tape

**An integral component of the UCC JointSeal Fabric Tape System.
Seals cracks and gaps to prevent water ingress.**

Description	UCC JointSeal Fabric Tape is a high strength laminar membrane based upon a paintable fabric backing laminated with an aggressively adhesive bitumen/butyl rubber adhesive layer.
Uses	UCC JointSeal Fabric Tape can be used in construction sector for sealing a variety of surfaces and prevent water ingress. It can be used for sealing roof sheet joints, flashing, roof penetrations, patching roofing membrane, gutter leaks and sealing joints between structural floor sheeting on decks and balconies. If exposed to UV, it can be top coated with acrylic, render etc.
Features	<ul style="list-style-type: none"> - High performance, paintable fabric backing layer - Designed for toughness and durability - Ease of field application - Adheres aggressively to a variety of primed substrates
Application	<ul style="list-style-type: none"> - Clean and dry substrate, optionally apply UCC Protek Butyl (Multi) Primer to cleaned substrate at spread rate of approximately 0.5 Ltr/m². - Lay UCC JointSeal Fabric Tape on substrate. - Use roller to firmly press tape into substrate.

Properties	Test Method	Value
Thickness	EN1849-1	1.2 mm Avg
Adhesion to steel	ASTM D1000 (18°C)	> 250 N
Adhesion to primed concrete	ASTM D1000 (18°C)	> 250 N
Tensile Strength	AS3706.2	7.5 kN/m
Tensile Elongation at Break	AS3706.2	50%
Impact Resistance	EN12691 Method A	20 mm
Puncture Strength (Ø8mm Rod)	ASTM D4833	310 N
Application Temperature		0°C to 50°C
Service Temperature		0°C to 70°C
Excursion Peak Temperature		80°C

Product Packaging			
Roll width (mm)	Roll Length (m)	Units / Carton	Carton Weight (kg)
50	10	12	5
100	10	8	6
150	10	6	12

Universal Corrosion Coatings Pty. Ltd.

16 Sperry Drive, Tullamarine, Victoria 3043, Australia

Phone: +61 3 9310 3515

Fax: +61 3 9310 3524

Website: www.unicc.com.au

The above information is given in good faith based on data and knowledge considered to be true and accurate and is offered for the user's assistance.