

# Manhole Sealing Grease

Providing assured long-term sealing of manhole frames and grates in the harshest environments.

<b>Description</b>	UCC Manhole Sealing Grease is composed of neutral petrolatum compound, stabilized with inert fillers and complemented with corrosion inhibitors. It is formulated to be plastic for its full service life.
<b>Uses</b>	UCC Manhole Sealing Grease is designed to provide assured permanent sealing of manhole frames and grates.
<b>Features</b>	<ul style="list-style-type: none"> <li>- Conforms to irregular shapes and profiles</li> <li>- Can be applied to cold damp substrates</li> <li>- Unaffected by water, acid, salts, or bacterial attack</li> <li>- Fortified with rust inhibitors</li> <li>- Nil VOC's</li> <li>- Ease of application at high and low temperature extremes</li> <li>- Ready for immediate service, no curing time</li> </ul>
<b>Application</b>	<ul style="list-style-type: none"> <li>- Clean the interface area.</li> <li>- Apply UCC Manhole Sealing Grease to substrate at spread rate of approximately 3 kg/m<sup>2</sup>.</li> </ul>

Properties	Value
Specific Gravity	1.0 mm
Solids Content	99.8%
Thickening Agent	Lithium
Spread Rate	3 kg/m <sup>2</sup>
Service Life	30 Years
Application Temperature	-10°C to 55°C
Service Temperature	-20°C to 115°C
Excursion Peak Temperature	120°C

Product Packaging			
Unit Size (kg)	Unit Packaging	Units / Carton	Carton Weight (kg)
4	Tub	4	17
20	Drum	1	21

**Universal Corrosion Coatings Pty. Ltd.**

16 Sperry Drive, Tullamarine, Victoria 3043, Australia

Phone: +61 3 9310 3515

Fax: +61 3 9310 3524

Website: [www.unicc.com.au](http://www.unicc.com.au)

The above information is given in good faith based on data and knowledge considered to be true and accurate and is offered for the user's assistance.